

Rohrdurchmesser d, DN Dichtungseinsatz und Schlüsselweite

Curaflex® A - F

Rohr-Ø von - bis	DN	Bolzen-Ø	Schlüsselweite
1 - 12	50	M 5	8
13 - 18			
19 - 24			
1 - 13	80	M 6	10
14 - 21			
22 - 28			
29 - 35			
36 - 40			
41 - 45	100	M 6	10
46 - 52			
53 - 57			
58 - 67	125	M 6	10
68 - 77			
78 - 85	150	M 6	10
86 - 94			
95 - 104			
105 - 115	200	M 8	13
116 - 124			
125 - 135		M 6	10
136 - 145			
146 - 156	250	M 8	13
157 - 165			
166 - 172			
173 - 179			
180 - 186			
187 - 190			
191 - 197	300	M 8	13
198 - 207			
208 - 215			
216 - 224			
225 - 233			

Curaflex® C/S, A/S

Rohr-Ø von - bis	DN	Bolzen-Ø	Schlüsselweite
9 - 14	100	M 6	10
15 - 21			
22 - 28			
29 - 35			
36 - 40			
58 - 65			
40 - 48	125	M 6	10
49 - 57			
58 - 67	130	M 6	10
68 - 77			
57 - 62	150	M 6	10
63 - 70			
71 - 77			
78 - 85	160	M 6	10
86 - 94			
95 - 104			
78 - 86	200	M 8	13
87 - 95			
96 - 104			
105 - 114	250	M 8	13
115 - 121			
122 - 129			
130 - 136			
137 - 145	300	M 8	13
158 - 168			
169 - 179			
180 - 190			

* Zuordnungen gelten nicht für Curaflex® C 40 und A 40.

Maximale Drehmomente

Bolzen-Ø	Schlüsselweite	Max. Drehmomente Curaflex® A - F
M 5	8	3 Nm
M 6	10	8 Nm
M 8	13	12 Nm
M 10	17	25 Nm
M 12	19	30 Nm

Bolzen-Ø	Schlüsselweite	Max. Drehmomente Curaflex® A 40/C 40
M 5	8	2 Nm
M 6	10	5 Nm
M 8	13	7 Nm
M 10	17	15 Nm
M 12	19	18 Nm

